

Features a redesigned print head system allowing for easier supply loading and quieter performance. Includes ethernet connectivity.

Key Features ▼

- Easy supply and print ribbon loading
- 3x print ribbon roll capacity (vs LT4)
- Quieter operation (vs LT4)
- 300 DPI resolution
- Standard USB 2.0 and ethernet ports
- Can manage supplies up to 4" wide

Plus, All Printers Include ▼

- Lifetime warranty on all parts/labor
- Lifetime support by phone, email or live chat
- Free shipping on orders to US and Canada. *(Some restrictions may apply)*
- 5 Year Label Guarantee

Common Applications ▼

- OSHA Compliance
- Equipment Safety
- Lean and 5S
- GHS and HazCom
- Warehouse/Racks
- Tool and Drawer ID
- Wayfinding
- Kanban
- Kaizen
- Pipe Marking
- Logistics
- Barcoding
- Product Marking
- ... and more



Technical Specifications ▼

Weight (lbs)	5.4 lbs (2.45 kg)
Physical Dimensions	8.82" (W) x 7.32" (H) x 11.57" (D) (224 mm x 186 mm x 294 mm)
Max Material Width	4.25" (108 mm)
Max Print Width	4.09" (104 mm)
Max Print Length	40.0" (1016 mm)
Bar Code Type	1D/2D
Connectivity	USB 2.0, Serial, Ethernet
Label Type	Can print both continuous and die-cut labels
Includes	Printer, USB Cable, Power Cable, Manual, Software
Materials Supported	LabelTac® Genuine Supplies
Connects to a PC	Yes
Power Supply	Universal AC Power Adapter AC Input: 100-240V-2.5A, 50-60Hz DC Output: 24V, 3.75A
Print Resolution	300 dpi
Print Speed	up to 4"/sec (102 mm/sec)
Print Technology	Thermal Transfer
Stand Alone Printing	Yes, w/ optional Label Design Workstation (p/n: LDW1)
Text Sizes	0.08" to 4.00" (2 mm - 102 mm)
Symbols/Templates	Hundreds Included
Warranty	LIFETIME Warranty on printer



LIFETIME WARRANTY

on all LabelTac® Models

"Bumper-to-bumper" warranty on all parts/labor.
If anything goes wrong- we've got your back!